

## Reolink-Go-Plus-Camera-Specifications

	Model	Reolink Go Plus
<b>Video &amp; Audio</b>	Image Sensor	1/3" CMOS Sensor
	Video Resolution	2560 x 1440 (4.0 megapixel) at 15 frames/sec
	Video Format	H.265
	Field of View	Fixed lens, horizontal: 95°; vertical: 52°; diagonal: 115°
	Infrared Night Vision	up to 10 meters (33ft) (LED: 6pcs/14mil/850nm)
	Digital Zoom	16x digital zoom
	Audio	Two-way audio
<b>PIR Detection &amp; Alerts</b>	Smart Alarm	PIR detection/person detection/vehicle detection
	PIR Detecting Distance	Adjustable up to 10m (33ft)
	PIR Detecting Angle	120° horizontal
	Audio Alert	Customizable verbal alerts
	Recording	Motion triggered recording
	Other Alerts	Instant email alerts and push notifications
<b>3G/4G</b>	Frequency Bands	Europe Version: LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8
		America Version: LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5
		Australia Version: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8
	Transmission Data	LTE FDD: Max. 10Mbps(DL), Max. 5Mbps(UL)
		LTE TDD: Max. 8.96Mbps(DL), Max. 3.1Mbps(UL)
HSPA+: Max. 42Mbps(DL), Max. 5.76Mbps(UL)		
UMTS: Max. 384Kbps(DL), Max. 384Kbps(UL)		
<b>Power</b>	Battery	7800mAh rechargeable battery (Battery life varies based on settings, usage & temperature.)
	Solar	Reolink Solar Panel
	DC Power	5V/2A USB power adapter
<b>Storage</b>	Local Storage	Supports up to 128GB micro SD card
	Cloud Storage	Supports Reolink Cloud (available in some countries)
<b>Smart Home</b>	Smart Home	Works with Google Assistant
<b>Working Environment</b>	Operating Temperature	-10°C to 55°C (14°F to 131°F)
	Weather Resistance	IP65 weatherproof
<b>Size &amp; Weight</b>	Size	Φ75 x 194mm (2.95 x 7.63 in)
	Weight (Battery Included)	450g (15.9oz)
<b>Warranty</b>	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> .